



10. ELECTRICAL CONNECTOR FOR LIGHTS IS STANDARD SIX PRONG. MATING VEHICLE CONNECTOR PROVIDED.
9. LOAD BANK HAS PROTECTIVE TRAVEL & STORAGE COVERS ON INTAKE & EXHAUSTS. THESE MUST BE REMOVED PRIOR TO OPERATION. SEE LOAD BANK MANUAL.
8. TRAILER HAS HYDRAULIC SURGE BRAKES WHICH ACTUATE BRAKES ON BOTH AXLES. SEE TRAILER MANUAL FOR DETAILS.
7. REVIEW TRAILER MANUAL, TOW VEHICLE MANUAL AND AVTRON MANUAL PRIOR TO TOWING.
6. TRAILER AXLE POSITION SET BY FACTORY BASED ON APPROXIMATELY 1000 LBS OF CABLE LOAD (WEIGHT) OR EQUIPMENT ADDED TO CABLE REELS. HITCH WEIGHT MUST BE BETWEEN 8-15% FOR PROPER TOWING. DO NOT BLOCK LOAD BANK INTAKE AREA IF EQUIPMENT ADDED TO FRONT DECK AREA.
- 5.
4. TRAILER RATING: 7000 LBS GVWR
3. DIMENSIONS ARE IN INCHES.
2. ALL DIMENSIONS ARE APPROXIMATE.
1. WEIGHT: 4800 LBS [2177 kg] LESS CABLE

NOTES:



TRAILER MOUNT LOAD BANK
GENERAL REFERENCE OUTLINE DRAWING

Model 5600

Rev -