



The Avtron Model 3103 are resistive, AC load banks designed for moveable, outdoor installation when up to 1100 kW of electrical load is required.

Capacity Ratings (kW)

Product Code	3 Ph Loading							1 Ph Loading						Control Circuit
	208V	220V	230V	380V	400V	440V	480V	120V	127V	230V	240V	254V	277V	
3103-1100-DBAB-B2AX	297	333	364	993	1100	-	-	65	73	240	261	293	348	380-420V 50Hz 3Ph

Load Step Resolution 1kW (using SIGMA II)

Overall Tolerance ±2.5% total capacity

Performance & Operation

Short Circuit Rating	10kA
Load Duration	100% load, continuous at rated Voltage. 10% above rated Voltage for short periods. ¹
Connection Options	Bus Bar: M12 single hole lug, 5 per phase, 2 x PE, 1 x N.
Instrumentation Accuracy	Class 0.5
Insulation Voltage - Power Circuit	1000V DC
Control Platform	SIGMA II

¹ short period is defined as 1 hour in 12.

Fan & Control Circuit

Fan & Control Circuit Consumption	50Hz - Nominal - 12A
Connection External/Internal	External: 32A 3ph + PE plug and socket conforming to IEC 60309-2 Internal: From supply on test
Recommended Protection	50Hz - 20A aM style fuse or equivalent

Design

Construction	2mm 'Zintec' steel, folded and welded to form a monocoque construction.
Elements	Stainless steel, non-finned sheathed elements
Finish	Grey RAL7042 - C3 Finish (ISO12944)
Lifting	4 point lift / Forklift pocket
Height	2328mm
Width	1724mm
Length	1724mm
Weight	1300kg

Environmental

Ambient Operating Temperature	-10°C to +50°C
Storage Temperature	-20°C to +70°C ²
Degree of Protection	All electrical enclosures to IP54
Operating Humidity	90% relative humidity, non-condensing
Operating Altitude	1000m ASL
Required Airflow (@50Hz)	7.5m³/sec
Required Airflow (@60Hz)	-
Average Air Temperature Rise	125°C at outlet
Hot Air Exhaust	Vertical
Noise Level	75dBA ±3dBA @ 50Hz, 3 meters from load bank at 90° to airflow direction


Standards & Compliance

Standards	  
Warranty	12 months

Optional Accessories

PVC Cover	PR01438
SIGMA LT Hand-held Control	EI02603
Trailer mount	-

Outline Drawing / Connection Diagram



All dimensions are in millimeters.
Specifications subject to change without notice.