



The 8200 is a 20 foot ISO containerized resistive load bank with capacities up to 5750kW and a wide option of voltages. Equipped with SIGMA load control enabling multiple options for testing, networking and data acquisition.

Capacity Rating (kVA @ 0.8pf)

Product Code	3ph Loading @ 1pf							1ph Loading @ 1pf						Control Circuit
	208V	220V	230V	380V	400V	440V	480V	120	127	230	240	254	277	
8200-5000-DBAB-B2AX	1352	1513	1653	4513	5000	-	-	297	333	1091	1188	1331	1583	380-420V 50Hz
8200-5750-HAAD-B2AX	1080	1208	1320	3604	3993	4832	5750	237	266	871	949	1063	1264	440-480V 60Hz

Load Step Resolution	1kW
Overall Tolerance	±2.5% total capacity

¹ Sigma will NOT allow +10% over voltage operation – max short term over V +6%

Performance & Operation

Short Circuit Rating	10kA
Load Duration	100% load, continuous at rated Voltage. 10% above rated Voltage for short periods.
Connection Options	Bus Bar: M12 single hole lug, 12 per phase, 10 x PE, 1 x Instrumentation Neutral.
Instrumentation Accuracy	Class 0.5
Insulation Voltage - Power Circuit	1000V DC
Control Platform	SIGMA II

² Short period is defined as 1 hour in 12.

Fan & Control Circuit

Connection External/Internal	125A 3ph, + PE plug and socket conforming to IEC 60309-2 From supply on test
Fan & Control Circuit Consumption	80A Nominal (60Hz)
Recommended Protection	80A aM style fuse or equivalent (60Hz)

Design

Construction	20ft ISO style container
Elements	Stainless steel, non-finned sheathed elements
Inductors	n/a
Finish	Grey RAL7042 - C3 Finish (ISO12944)
Lifting	4 point lift via x4 corner ISO castings / Forklift pocket
Height	2591mm
Width	2438mm
Length	6058mm
Max Weight	9000kg

Environmental

Ambient Operating Temperature	-10°C to +50°C
Storage Temperature	-20°C to +70°C
Degree of Protection	All electrical enclosures to IP55
Operating Humidity	90% relative humidity, non-condensing
Operating Altitude	1000m ASL
Required Airflow (@50Hz)	28m3/sec - measurements are combined for both ducts
Required Airflow (@60Hz)	35m3/sec - measurements are combined for both ducts
Average Air Temperature Rise	146°C at duct outlet (50Hz) / 138°C at duct outlet (60Hz)
Hot Air Exhaust	Vertical
Noise Level	88dBA ±3dBA @ 50Hz

³ Battery life in the SIGMA LT control panel may be reduced if stored outside of 0°C to +30°.

⁴ Taken 3 meters from load bank at 90° to airflow direction

Standards & Compliance

Standards	  
Warranty	24 months

Optional Accessories

Sigma Handheld and 10m Lead	EI02603
-----------------------------	---------

Outline Drawing / Connection Diagram

